穒

4

蔀



特性:

- ■通用性强
- ■1x15"超低音系統
- ■雙諧振腔倒相設計

Features:

- ■Versatility
- ■1x15 "subwoofer system
- ■Dual resonate cavity paraphase design

BS150是一款雙諧振腔倒相設計低頻揚聲器,裝載1衹15"低頻驅動單元,頻率響 應特性42Hz~200Hz,低頻輸出更具有深沉和震撼的感覺。BS150使用多層膠合 板制造箱體,環保塗層保護外殼,音箱采用三角形網孔金屬網罩内貼聲學透聲 海綿作揚聲器保護,側面板融合了4個把手,後面板還配置有16個滑輪安裝螺絲 ,頂部裝有M20的螺口用于支撑其它全頻音箱,接綫板裝有NL4并行接口。當 多衹BS150堆叠在一起時,箱體底部的4個橡膠墊可嵌入另一衹音箱的凹槽裏面 防止音箱滑動。

Description:

BS150 is a dual resonate cavity paraphase design subwoofer, it loads a 15" longstroke LF driving unit, 42Hz-200Hz frequency response characteristic. LF ouput has a feeling of deep and shocking. BS150 uses multilayer birch plywood to make the enclosure, with elastic coating or environmental protection coating shell. The $\,$ front panel use metal mesh enclosure stick acoustic soft sponge as the speaker's protection. Side plate combine 4 handles and wheel plate buckles, also dispose with 16 pulley mounting screw in rear panel. Terminal is disposed with NL4 parallel connection, M20 supporting base for other full range speaker both on top and side plate. When more than one BSI50 stacked together, there are 4 rubber pads at the bottom of each speaker could be embedded to the groove of others, in order to aviod sliding.

應用:

- ■大型政企活動
- ■迪廳、歌舞廳、俱樂部
- ■夜總會、卡拉OK包房
- ■固定安裝

Applications:

- ■Large government and enterprise activities
- ■Disco, dance halls, clubs
- ■Nightclubs, karaoke rooms
- Fixed installation install

Specifications規格

System 玄統

System 未规	
Frequency Response 頻響	42 Hz - 200 Hz @(±3 dB)
Sensitivity 系統靈敏度	99 dB SPL (IW @ Im)
Nominal Impedance 阻抗	8 ohms
Power Handing 功率	600 watts (rms額定), I 200 watts (program節目), 2400 watts (peak最大)
Maximum SPL 最大聲壓	125 dB
Crossover Frequency 分頻點	120 Hz

Component Elements 系統組件

Low Frequency 低頻 I x I5(in) 380 mm dia (直徑) , I 00 mm(4in)voice coil dia (音圏直徑)

PHYSICAL 箱體

Enclosure Construction 箱殼	18 mm plywood with structured(膠合板)
Finish 表面	Wear-resistant textured black paint (黑色耐磨粗點噴漆)
Grille 面罩	Powder coated perforated steel,foam backed(鐵網、内貼透氣棉)
Options 其它	Aluminium pole mount socket(鋁合金支撑底座)
Input Connectors 連接器	Speakon NL4 x 2
Dimensions 尺寸 H x W x D	617 mm x 474 mm x 570 mm
Net Weight 重量	32 kg

Overall dimensions







Тор