BS-SERIES

MODEL: BS180 Ix18" Subwoofer System 超低音系統



BS180是一款雙諧振腔倒相式設計的超低頻揚聲器,裝載1衹18"大功率低頻驅動 單元, 低頻低沉有力, 適合作爲固定安裝使用, 與其它音響系統多種搭配使用 作爲低頻擴展, 頻率響應特性37Hz~200Hz。BS180使用多層膠合板制造箱體 、環保塗層保護外殼,音箱前面板采用金屬網罩内貼聲學透聲海綿作揚聲器保 護, 側面板融合了8個把手, 後面板還配置有16個滑輪安裝螺絲, 接綫板裝有 NL4并行接口。當多衹BS180堆叠在一起時,箱體底部的4個橡膠墊可嵌入另一 衹音箱的凹槽裏面防止音箱滑動。

Description:

BS180 is a dual resonate cavity paraphase design subwoofer, it loads 1×18 " big power LF drive unit, LF output is deep and strong. It's suitable to use as a fix installation or to be a LF extension that various using with other audio system, 37Hz-200Hz frequency response characteristic.BS180 uses multilayer birch plywood to make the enclosure, with elastic coating or environmental protection coating shell. The front panel use metal mesh enclosure stick acoustic soft sponge as the speaker's protection. Side plate combine 8 handles and wheel plate buckles, also dispose with 16 pulley mounting screw in rear panel. Terminal is disposed with NL4 parallel connection. When more than one BS180 stacked together, there are 4 rubber pads at the bottom of each speaker could be embedded to the groove of others, in order to aviod sliding.

特性:

- ■通用性强
- ■1x18"超低音系統
- ■雙諧振腔倒相設計

Features:

 α

- ■Versatility
- ■Ix18 "subwoofer system
- ■Dual resonate cavity paraphase design

應用:

- ■大型政企活動
- ■迪廳、歌舞廳、俱樂部
- ■夜總會、卡拉OK包房
- ■固定安裝安裝

Applications:

- ■Large government and enterprise activities
- ■Disco, dance halls, clubs
- ■Nightclubs, karaoke rooms
- Fixed installation install

Specifications規格

System 余航	
Frequency Response 頻響	37 Hz - 200 Hz @(±3 dB)
Sensitivity 系統靈敏度	99 dB SPL (IW @ Im)
Nominal Impedance 阻抗	8 ohms
Power Handing 功率	800 watts (rms額定), I 600 watts (program節目), 3200 watts (peak最大)
Maximum SPL 最大聲壓	129 dB
Crossover Frequency 分頻點	120 Hz

Component Elements 系統組件

Low Frequency 低頻 I x I8(in) 460 mm dia (直徑) , I 00 mm(4in)voice coil dia (音圏直徑)

PHYSICAL 箱體

The second secon	
Enclosure Construction 箱殻	18 mm plywood with structured(膠合板)
Finish 表面	Wear-resistant textured black paint(黑色耐磨粗點噴漆)
Grille 面罩	Powder coated perforated steel,foam backed(鐵網、内貼透氣棉)
Options 其它	Aluminium pole mount socket(鋁合金支撑底座)
Input Connectors 連接器	Speakon NL4 x 2
Dimensions 尺寸 H x W x D	736 mm x 510 mm x 640 mm
Net Weight 重量	40.5 kg

Overall dimensions







