起時,箱體底部的4個橡膠墊可嵌入另一衹音箱的凹槽裏面防止音箱滑動。

BS250 is a paraphase design subwoofer, it loads 2x15" big power LF drive unit, LF output is deep and strong. It's suitable to use as a fix installation or to be a LF extension that various using with other audio system, 36Hz-200Hz frequency response characteristic.BS250 uses multilayer birch plywood to make the enclosure, with elastic coating or environmental protection coating shell. The front panel use metal mesh enclosure stick acoustic soft sponge as the speaker's protection. Side plate combine 8 handles and wheel plate buckles, also dispose with 16 pulley mounting screw in rear panel. Terminal is disposed with NL4 parallel connection. When more than one BS250 stacked together, there are 4 rubber pads at the bottom of each speaker could be embedded to the groove of others, in order to aviod sliding.

應用:

- ■大型政企活動
- ■迪廳、歌舞廳、俱樂部
- ■夜總會、卡拉OK包房
- ■流動或固定安裝

Applications:

- ■Large government and enterprise activities
- ■Disco, dance halls, clubs
- ■Nightclubs, karaoke rooms
- Fixed installation install



- ■2x15"超低音系統
- ■倒相式設計
- ■提供强勁的低頻能量輸出

Features:

- ■2x15 "subwoofer system
- ■Paraphase design
- ■Versatility

Specifications規格

System 未规	
Frequency Response 頻響	36 Hz - 200 Hz @(±3 dB)
Sensitivity 系統靈敏度	105 dB SPL (IW @ Im)
Nominal Impedance 阻抗	4 ohms
Power Handing 功率	I 000 watts (rms額定), 2000 watts (program節目), 4000 watts (peak最大)
Maximum SPL 最大聲壓	130 dB
Crossover Frequency 分頻點	120 Hz


Component Elements 系統組件

Low Frequency 低頻 2 x I 5(in) 380 mm dia (直徑) , I 00 mm(4in)voice coil dia (音圏直徑)

PHYSICAL 箱體

Enclosure Construction 箱殼	I8mm plywood with structured(膠合板)
Finish 表面	Wear-resistant textured black paint (黑色耐磨粗點噴漆)
Grille 面罩	Powder coated perforated steel,foam backed(鐵網、内貼透氣棉)
Options 其它	Aluminium pole mount socket(鋁合金支撑底座)
Input Connectors 連接器	Speakon NL4 x 2
Dimensions 尺寸 H x W x D	480 mm x 960 mm x 651 mm
Net Weight 重量	49 kg

Overall dimensions







Side

Тор

THE BEST OF BEST

糕

4

華