



### 描述:

BS280是一款倒相式設計的超低頻揚聲器,裝載2x18"大功率低頻驅動單元,低頻低沉有力,適合作為固定安裝使用,與其它音響系統多種搭配使用作為低頻擴展,頻率響應特性37Hz~200Hz。BS280使用多層膠合板製造箱體、環保塗層保護外殼,音箱採用三角形網孔金屬網罩內貼聲學透聲海綿作揚聲器保護,側面板融合了8個把手,後面板還配置有16個滑輪安裝螺絲,接綫板裝有NL4并行接口。當多祇BS280堆疊在一起時,箱體底部的4個橡膠墊可嵌入另一祇音箱的凹槽裏面防止音箱滑動。

### Description:

BS280 is a paraphase design subwoofer, it loads 2x18" big power LF drive unit, LF output is deep and strong. It's suitable to use as a fix installation or to be a LF extension that various using with other audio system, 37Hz-200Hz frequency response characteristic. BS280 uses multilayer birch plywood to make the enclosure, with elastic coating or environmental protection coating shell. The front panel use metal mesh enclosure stick acoustic soft sponge as the speaker's protection. Side plate combine 8 handles and wheel plate buckles, also dispose with 16 pulley mounting screw in rear panel. Terminal is disposed with NL4 parallel connection. When more than one BS280 stacked together, there are 4 rubber pads at the bottom of each speaker could be embedded to the groove of others, in order to avoid sliding.

### 特性:

- 2x18"超低音系統
- 倒相式設計
- 提供強勁的低頻能量輸出
- 通用性強

### Features:

- 2x18 "subwoofer system
- Paraphase design
- Powerful LF output
- Versatility

### 應用:

- 大型政企活動
- 迪廳、歌舞廳、俱樂部
- 夜總會、卡拉OK包房
- 固定安裝安裝

### Applications:

- Large government and enterprise activities
- Disco, dance halls, clubs
- Nightclubs, karaoke rooms
- Fixed installation install

### Specifications規格

#### System 系統

|                         |   |
|-------------------------|---|
| Frequency Response 頻響   | 37 Hz - 200 Hz @ (±3 dB)  |
| Sensitivity 系統靈敏度       | 105 dB SPL (1W @ 1m)  |
| Nominal Impedance 阻抗    | 4 ohms  |
| Power Handling 功率       | 1600 watts (rms額定), 3200 watts (program節目), 6400 watts (peak最大) |
| Maximum SPL 最大聲壓        | 135 dB  |
| Crossover Frequency 分頻點 | 110 Hz  |

#### Component Elements 系統組件

|                  |   |
|------------------|---|
| Low Frequency 低頻 | 2 x 18(in) 460 mm dia (直徑), 100 mm(4in) voice coil dia (音圈直徑) |
|------------------|---|

#### PHYSICAL 箱體

|                           |  |
|---------------------------|--|
| Enclosure Construction 箱殼 | 18 mm plywood with structured (膠合板)                    |
| Finish 表面                 | Wear-resistant textured black paint (黑色耐磨粗點噴漆)         |
| Grille 面罩                 | Powder coated perforated steel, foam backed (鐵網、內貼透氣棉) |
| Input Connectors 連接器      | Speakon NL4 x 2  |
| Dimensions 尺寸 H x W x D   | 526 mm x 1200 mm x 720 mm                              |
| Net Weight 重量             | 67.5 kg  |

### Overall dimensions

