



### 特性:

- 高效徑向磁路設計驅動器
- 2X15"超低系統
- 帶通技術
- 高效能低頻輸出
- 一體化陣列連接組件
- 可與AS320/AS340同時吊掛

### Features:

- High efficiency radial magnet circuit driver
- 2X15" subwoofer system
- Bandpass technology
- High efficiency LF output
- Integrated array connection device
- Suspend with AS320/AS340

### 描述:

BS320是一款採用帶通設計的超低頻揚聲器，裝載了2x15"高效能徑向磁路低頻驅動單元，高效能大功率輸出。該系統用于AS320/AS340系統作低頻擴展，配套的懸掛裝置可與AS320/AS340音箱組合連接成一套高效能陣列系統。能够應用于各種不同的組合；如地面堆疊或吊掛，也可將它安裝于AS320/AS340陣列的頂部或作為獨立的低頻音箱組。BS320使用多層樺木膠合板制造箱體，表面塗有專用耐磨的抗撞彈性塗料保護外殼，音箱採用六角形網孔金屬網罩內貼聲學透聲海綿作揚聲器保護，側面板融合了多個把手以及吊掛裝置。背板上裝有NL8并行接口。

### Description:

BS320 is a bandpass design subwoofer. It loads 2x15" high efficiency radial magnetic path LF drive units, efficiency and powerful output. This system is used as LF extension of AS320/AS340 system, its suspension device can be combined with AS320/AS340 system to become a high efficiency array system. It can be applied to different assembly such as stacking on the ground or hanging. BS320 uses multilayer birch plywood to make the enclosure, with elastic coating or environmental protection coating shell. The front panel uses metal mesh enclosure with acoustic soft sponge as the speaker's protection. Side panel combines handles and suspension device, NL8 parallel connection on rear panel.

### 應用:

- 大型體育館、運動場、各類演出活動
- 娛樂場所、夜總會、酒吧
- 主題公園、音樂廳
- 流動或固定安裝
- 作為AS320/340系統的低頻部分

### Applications:

- Large stadiums, arenas, all kinds of performances
- Entertainment venues, nightclubs, bars
- Theme park and concert hall
- Mobile or fixed installation
- As subwoofer of AS320/340 system

## Specifications規格

### System 系統

Frequency Range 頻響	45 Hz - 250 Hz @ (±3 dB)
Sensitivity 系統靈敏度	106dB SPL (1W @ 1m)
Nominal Impedance 阻抗	2x8 ohms/4 ohms
Power Handling 功率	800 watts (rms額定), 1600 watts (program節目), 3200 watts (peak最大)
Maximum SPL 最大聲壓	136 dB
Crossover Frequency 分頻點	100 Hz

### DRIVERS 驅動器

Low Frequency (neodymium magnet) 鈹鐵磁低音	2 x 15(in) 310 mm dia (直徑), 2x75 mm(3in)voice coil dia (音圈直徑)
--	---

### PHYSICAL 箱體

Enclosure Construction 箱殼	15 mm birch plywood with structured (樺木夾板)
Finish 表面	Wear-resistant textured black paint (黑色耐磨粗點噴漆)
Grille 面罩	Powder coated perforated steel, foam backed (鐵網、內貼透氣棉)
Suspension Hardware 吊掛件	Proprietary BOB rigging system (專用套件)
Input Connectors 連接器	Speakon NL8 x 2
Dimensions 尺寸 H x W x D	490 mm x 930 mm x 681 mm
Net Weight 重量	38 kg

## Overall dimensions

