FNS

FNS-SERIES

MODEL: FBS6015



FBS6015是一款倒相式設計的超低頻揚聲器,裝載1衹15"大功率低頻驅動單 元,低頻低沉有力,適合作爲固定安裝使用,與其它音響系統多種搭配使 用作爲低頻擴展,頻率響應特性45Hz~200Hz。FBS6015使用多層特制膠 合板制造箱體、環保水性塗層保護外殼, 音箱前面板采用金屬網罩內貼聲 學透聲海綿作揚聲器保護,側面板融合了4個金屬壓鑄把手,後面板還配置 有16個滑輪安裝螺絲,頂部裝有M20的螺口用于支撑其它全頻音箱,接綫 板裝有NL4并行接口。當多衹FBS6015堆叠在一起時,箱體底部的4個橡膠 墊可嵌入另一衹音箱的凹槽裏面防止音箱滑動。

Description:

FBS6015 is a phase-inversed subwoofe. Loading 1 x 15" low frequency driver, LF is low and powerful, good for permanent installation, use with other sound system of supplement, its low frequency response range is 45Hz-200Hz. FBS6015 uses multilayer birch plywood to make the enclosure, with environmental protection coating shell. The front panel use metal mesh enclosure stick acoustic soft sponge as the speaker's protection. Side plate combine 4 handles and wheel plate buckles, also dispose with 16 pulley mounting screw in rear panel and M20 screw mount for support, terminal is disposed with NL4 parallel connection. When more than one FBS6015 stacked together, there are 4 rubber pads at the bottom of each speaker could be embedded to the groove of others, in order to avoid sliding.

- 特性: ■通用性强
- ■1x15"超低音系統
- ■直射式前導相

Options 其它

Net Weight 重量

Input Connectors 連接器

Dimensions 尺寸HxWxD:

- Features: ■Versatility
- 1x15 "subwoofer system
- ■Direct shooting front phase-inverted tube

應用:

- ■大型政企活動
- ■迪廳、歌舞廳、俱樂部

Aluminium pole mount socket(鋁合金支撑底座)

- ■夜總會、卡拉OK包房
- ■固定安裝安裝

Speakon NL4 x 2

30.93 kg


440 mm x 500 mm x 530 mm


Applications:

- ■Large government and enterprise activities
- ■Disco, dance halls, clubs
- ■Nightclubs, karaoke rooms
- ■Fixed installation install

Specifications規格	
System 系統	
Frequency Response 頻響	45 Hz - 200 Hz @(±3 dB)
Sensitivity 系統靈敏度	98 dB SPL (IW @ Im)
Nominal Impedance 阻抗	8 ohms
Power Handing 功率	800 watts (rms額定) , I 600 watts (program節目) , 3200 watts (peak最大)
Maximum SPL 最大聲壓	127 dB
Crossover Frequency 分頻點	135 Hz
Component Elements 系統組件 Low Frequency 低頻	I × I5(in) 385 mm dia(直徑), I 00 mm(4in)voice coil dia(音圈直徑)
LOW Frequency 版源	TX T3(III) 363 IIIII dia(直压), T00 IIIII(4III) Voice coil dia(自固直压)
PHYSICAL 箱體	
Enclosure Construction 箱殼	I8 mm Plywood (特制膠合板)
Finish 表面	Wear-resistant textured black paint(環保水性黑色耐磨粗點噴漆)
Grille 面罩	Powder coated perforated steel,foam backed(鐵網、内貼透氣棉)
- 44 ->-	4 - 4 - 4 - 1 - 100 - 3 - 3

Overall dimensions







Тор