FNS

FNS-SERIES

MODEL: FBS6018



FBS6018是一款倒相式設計的超低頻揚聲器,裝載1衹18"大功率低頻驅動單 元,低頻低沉有力,適合作爲固定安裝使用,與其它音響系統多種搭配使 用作爲低頻擴展,頻率響應特性40Hz~250Hz。FBS6018使用多層特制膠 合板制造箱體、環保水性塗層保護外殼, 音箱前面板采用金屬網罩內貼聲 學透聲海綿作揚聲器保護,側面板融合了4個金屬壓鑄把手,後面板還配置 有16個滑輪安裝螺絲,頂部裝有M20的螺口用于支撑其它全頻音箱,接綫 板裝有NL4并行接口。當多衹FBS6018堆叠在一起時,箱體底部的4個橡膠 墊可嵌入另一衹音箱的凹槽裏面防止音箱滑動。

Description:

FBS6018 is a phase-inversed subwoofe. Loading 1 x 18" low frequency driver, LF is low and powerful, good for permanent installation, use with other sound system of supplement, its low frequency response range is 40Hz-250Hz. FBS6018 uses multilayer birch plywood to make the enclosure, with environmental protection coating shell. The front panel use metal mesh enclosure stick acoustic soft sponge as the speaker's protection. Side plate combine 4 handles and wheel plate buckles, also dispose with 16 pulley mounting screw in rear panel and M20 screw mount for support, terminal is disposed with NL4 parallel connection. When more than one FBS6018 stacked together, there are 4 rubber pads at the bottom of each speaker could be embedded to the groove of others, in order to aviod sliding.

特性:

- ■通用性强
- ■1x18"超低音系統
- ■直射式前導相

Features:

- ■Versatility
- Ix I8 "subwoofer system
- ■Direct shooting front phase-inverted tube

應用:

- ■大型政企活動
- ■迪廳、歌舞廳、俱樂部
- ■夜總會、卡拉OK包房
- ■固定安裝安裝

Applications:

- ■Large government and enterprise activities
- ■Disco, dance halls, clubs
- ■Nightclubs, karaoke rooms
- ■Fixed installation install

Specifications規格

System 系绘

System 永航	
Frequency Response 頻響	40 Hz - 250 Hz @(±3 dB)
Sensitivity 系統靈敏度	99 dB SPL (IW @ Im)
Nominal Impedance 阻抗	8 ohms
Power Handing 功率	800 watts (rms額定) , I 600 watts (program節目) , 3200 watts (peak最大)
Maximum SPL 最大聲壓	128 dB
Crossover Frequency 分頻點	135 Hz

Component Elements 系統組件

I x I8(in) 460 mm dia (直徑) , 99.5 mm(4in)voice coil dia (音圈直徑) Low Frequency 低頻

PHYSICAL 箱體

Enclosure Construction 箱殼	I8mm Plywood(特制膠合板)
Finish 表面	Wear-resistant textured black paint (環保水性黑色耐磨粗點噴漆)
Grille 面罩	Powder coated perforated steel,foam backed (鐵網、内貼透氣棉)
Options 其它	Aluminium pole mount socket(鋁合金支撑底座)
Input Connectors 連接器	Speakon NL4 x 2
Dimensions 尺寸HxWxD:	510 mm x 665 mm x 605 mm
Net Weight 重量	43.25 kg

Overall dimensions





