



特性:

- 全頻多功能線性音柱系統
- 有效控制聲音傳播方向和範圍
- 多種顏色可選、容易融入建築風格
- 鋁合金壓鑄箱體
- 覆蓋水平範圍寬廣
- 清晰的語音表現
- 多個揚聲器可進行級聯
- 阻抗切換
- 專屬吊裝組件
- 全天候設計、適合戶外安裝

Features:

- Full range multi-function linear sound column system
- Effectively control sound direction and coverage
- Multi color,easy for building matching
- Aluminum alloy cabinet
- Wide coverage
- Clear sound
- Different speaker can connect
- Resistent switch
- Special flying parts
- Suible for outdoor use

描述:

LS8308是一款全頻多用途線性音柱揚聲器，根據線性陣列原理設計。裝載了8x3"鈹磁全頻驅動單元，任秀優雅的外形設計，語音清晰自然真實。良好的覆蓋範圍使得它可以選擇垂直或水平安裝。同時也可以多祇揚聲器級聯或組成陣列使用。具有0° - 78°可選調節垂直覆蓋範圍(每隔13°可調)，配合其它系列超低頻擴展低頻段。適用於多種條件下的室內固定安裝或臨時表演使用，給商業建築環境中的聲音分布提供有效解決方法和應用。LS8308使用高品質鋁合金壓鑄箱體、堅固環塗層保護外殼，多種顏色可選。音箱採用圓孔金屬網罩內貼聲學透聲海綿作揚聲器保護，音箱背面預留了12個4mm級聯和固定安裝的組件安裝孔，接線板裝有NL4并行接口。

Description:

LS8308 is a full range multi using sound column speaker,designed according to line array theory.Loaded with 8x3" neo full range units,slim and elegant look,sound clear,natrural and true.The good coverage range make it suitable for vertical and horizontal flying.Can connect several driver to form array use.0° - 78°vertical angel adjustable(13°each step),matching other subwoofer speaker to use.Suitable for all indoor permanent installation conditions or temporary use,provide effctive solution and applycation to commercial building environment sound distribution.LS8308 is made of high quality aluminium alloy die castcabinet,strong environmental paint,multi-color for choose.Covered by round hole metal grille(sticked acoustic sound through foam inside),there are 12pcs 4mm connect and permanant installatioin hole in the back,and with NL4 parallel interface.

應用:

- 宗教場所、禮堂
- 會議室、多用途空間
- 娛樂場所、餐廳和酒吧
- 交通設施、體育場館
- 圖書館、博物館
- 購物中心、學校
- 小型表演、演講

Applications:

- Religion place,auditorium
- Meeting room,multi-function place
- Entertainment places,canteen,bar
- Trafic place,stadium
- Library,museum
- Shopping center,school
- Small show,speech

Specifications規格

System 系統

Frequency Range 頻響	150 Hz - 20 kHz @ (± 3 dB)
Sensitivity 系統靈敏度	97 dB SPL (1W @ 1m)
Nominal Impedance 阻抗	4 ohms/16 ohms
Power Handing 功率	280 watts (rms額定), 560 watts (program節目), 1120 watts (peak最大)
Maximum SPL 最大聲壓	123 dB
Crossover Frequency 分頻點	150 Hz

DRIVERS 驅動器

Low Frequency 低頻	8 x 3(in) 89 mm dia (直徑), 25 mm(1in)voice coil dia (音圈直徑)
------------------	---

PHYSICAL 箱體

Enclosure Construction 箱殼	Aluminum alloy cabinet (鋁合金)
Finish 表面	White or black paint (白色或黑色噴漆)
Input Connectors 連接器	Speakon NL 4x2
Dimensions 尺寸 H x W x D	780 mm x 110 mm x 120 mm
Net Weight 重量	10 kg

Overall dimensions

