



描述:

MS10是一款二頻電影環繞聲揚聲器，向下20°傾斜箱體設計。裝載10"低音單元和1.33"高頻壓縮驅動器。多邊型的90° x90° 號角覆蓋範圍，主要安裝于影院中作環繞聲道、多音軌聲道重播使用。MS10使用15mm高密度板制造箱體、堅固環保塗層保護外殼，聲學透聲網布制作揚聲器保護外罩，頂部和側面各裝置了2顆M8吊裝螺絲，接線合裝有旋鈕式接線柱。使用標配吊裝組件，安裝簡潔方便。

Description:

MS10 is a 2 way surrounding speaker, down 20° tilt cabinet design. loaded with 10" LF unit and 1.33" HF unit. Polygon 90°x90° horn coverage, use for surrounding, multi sound channel replay. MS10 is made of 15mm high density wood cabinet, strong environmental paint and acoustic cloth for covering. The top and side is equipped with 2xM8 screws each. Knob wire. Standard flying parts, simple and convenient for installing.

特性:

- 無須組裝、安裝簡便
- 二路全頻系統
- 箱體輕巧
- 90° x90° 覆蓋範圍
- 向下20° 投射箱體設計
- 符合THX標準

Features:

- No need assemble, convenient for installing
- 2 way full range system
- Light cabinet
- 90°x90° coverage
- Downward 20° shooting
- According to THX standard

應用:

- 中小型電影院、影廳
- 後期制作設備
- 私人定制影院

Applications:

- Middle small size cinema
- Post production
- Private cinema

Specifications 規格

System 系統

Frequency Response 頻響	60 Hz - 20 kHz @ (± 3 dB)
Sensitivity 靈敏度	94dB SPL (1W @ 1m)
Nominal Impedance 阻抗	8 ohms
Power Handling 功率	180 watts (rms額定), 360 watts (program節目), 720 watts (peak最大)
Maximum SPL 最大聲壓	117 dB
Nominal Dispersion 指向性	90° horizontal (水平), 90° vertical (垂直)
Crossover Frequency 分頻點	2.2 kHz

DRIVERS 驅動器

Low Frequency 低頻	1 x 10(in) 260 mm dia (直徑), 50 mm(2in) voice coil dia (音圈直徑)
High Frequency 高頻	1 x 1.33(in) 34 mm voice coil dia (音圈直徑), 23 mm(1in) throat dia (喉徑)

PHYSICAL 箱體

Enclosure Construction 箱殼	18 mm Medium Density Fiberboard (中纖板)
Finish 表面	Wear-resistant textured black paint (黑色耐磨粗點噴漆)
Grille 面罩	Grey acoustically transparent cloth grille (灰色布網罩)
Input Connectors 連接器	binding posts (兩位接線柱)
Dimensions 尺寸 H x W x D:	540 mm x 520 mm x 260 mm
Net Weight 重量	13.5 kg

Overall dimensions

