



### 描述:

NST15是一款二路同軸全頻多用途揚聲器。採用一個固定的指向性圓錐形波導管和3"鈦膜高頻壓縮驅動單元、15"低頻驅動單元精巧地裝嵌在一起組成同軸揚聲器，提供固定60°軸對稱指向性輸出。由於採用了同軸設計以及時間校準技術，使音箱更接近理想中的點聲源，因此音箱發出的聲音具有很強的臨場感、很好的清晰度，以及很強的聲反饋抑制能力。NST15使用多層樺木膠合板製造箱體、堅固環保塗層保護外殼，音箱採用六角網孔金屬網罩內貼聲學透聲海綿作揚聲器保護，頂底板各有1個一體化木質把手，接線板裝有NL4并行接口和雙功放或全頻驅動開關。音箱頂底端配有一對圓形吊裝附件，以實現多用途之功能。

### Description:

NST15 is a 2 way full range multi use speaker, a firm directing cone shape horn, 3" titanium compression driver and 15" LF unit elaborately combine together to form a coaxial driver, provide firm 60° Axisymmetric output. The coaxial and time correcting design make the speaker approach the point source, the outcome sound is more real, clear, and feedback inhibition is stronger. NST15 is made of multi-layer birch plywood cabinet, strong environmental paint. Hex hole grille stuck with acoustic foam inside for protect, there is 1 integrated wood handle on top and bottom. NL4 parallel wire pole and switch for full range/bi-amp. One pair round flying parts is prepared on top and bottom, for multi use.

### 特性:

- 二路全頻同軸揚聲器
- 單點聲源輻射軸對稱60°指向性
- 覆蓋準確, 聲音清晰
- 極具魅力的人聲表現
- 多功能箱體設計
- 吊裝附件安裝方便靈活

### Features:

- 2 way full range coaxial speaker
- Single point source Axisymmetric 60°
- Accurately cover, clear sound
- Charming human voice performance
- Multi-function cabinet design
- Convenient and flexible for flying

### 應用:

- 迪廳、舞臺、演藝俱樂部
- 酒吧、夜總會、KTV包房
- 舞台補聲
- 永久固定安裝

### Applications:

- Disco, stage, club
- Bar, night club, KTV room
- Stage sound reinforcement
- Permanent installation

## Specifications 規格

### System 系統

Frequency Response 頻響	60 Hz - 18 kHz (± 3 dB)
Sensitivity 靈敏度	98 dB SPL (1W @ 1m)
Nominal Impedance 阻抗	8 ohms
Power Handling 功率	500 watts (rms額定), 1000 watts (program節目), 2000 watts (peak最大)
Maximum SPL 最大聲壓	128 dB
Nominal Dispersion 指向性	50° (± 10°) (軸對稱)
Crossover Frequency 分頻點	1.0 kHz

### DRIVERS 驅動器

Low Frequency (neodymium magnet) 低音	1 x 15(in) 380 mm dia (直徑), 75 mm(3in) voice coil dia (音圈直徑)
High Frequency (neodymium magnet) 高音	1 x 3(in) 75 mm voice coil dia (音圈直徑)

### PHYSICAL 箱體

Enclosure Construction 箱殼	15 mm birch plywood with structured (樺木夾板)
Finish 表面	Wear-resistant textured black paint (黑色耐磨粗點噴漆)
Grille 面罩	Powder coated perforated steel, foam backed (鐵網、內貼透氣棉)
Rigging 懸掛	Proprietary BOB rigging system (專用套件)
Input Connectors 連接器	Speakon NL4 x 2
Dimensions 尺寸 H x W x D:	630 mm x 437 mm x 450 mm
Net Weight 重量	30 kg

### Overall dimensions

